



TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1000 to glue























Permanently elastic polyurethane flooring according to EN 16776
Without the addition of chlorin, without plasticisers or solvents.

wineo

 Dryback	wood XXS	wood XS	stone XS	wood L	wood XL	stone L
Format	380 x 95 mm	480 x 80 mm	480 x 80 mm	1298 x 199 mm	1500 x 250 mm	645 x 335 mm
Product thickness	2.2 mm	2.2 mm	2.2 mm	2.2 mm	2.2 mm	2.2 mm
Weight	3.0 kg/m ²	3.0 kg/m ²	3.0 kg/m ²	3.0 kg/m ²	3.0 kg/m ²	3.0 kg/m ²
Planks / m² per box	45 / 1.62 m ²	45 / 1.73 m ²	45 / 1.73 m ²	20 / 5.17 m ²	14 / 5.25 m ²	22 / 4.75 m ²
Boxes / m² per pallet	168 / 272.16 m ²	144 / 249.12 m ²	144 / 249.12 m ²	60 / 310.20 m ²	56 / 294 m ²	66 / 313.50 m ²








Guarantee Life Time Guarantee for private use according to Windmüller warranty conditions – www.wineo.de

Classification		Product composition
 Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1 Top element • PU-top layer with surface structure • decor paper • stabilisation
 Utilization class 32 EN ISO 10874	Commercial sector with average usage	
Scratch resistance EN 16776, annex A	Utilization class 23: > 3 N Utilization class 32: > 5 N	2 Base layer ecuran high performance composite material
 R9 Anti slip category DIN 51130	R 9	
 Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	3 Backing Integrated Fleece TEC System
 Light fastness EN ISO 105-B02	~ 7	
 Residual indentation EN ISO 24343-1	≤ 0.10 mm	         
 Effect of a furniture leg EN 424	Utilization class 23: Foot type 3 Utilization class 32: Foot type 2 no visible change	
 Castor chair test EN 425	25000 revolutions no damage with rolls type W	
 Thermal resistance ISO 8302	0.01 (m ² K)/W	
 Impact sound reduction EN ISO 10140	~ 4 dB ~ 17 dB in the system with silentPLUS	
 Dimension stability EN ISO 23999	≤ 0.15 %	
 Flexural behaviour EN ISO 24344	≥ 20 mm	
REACH	free from SVHC substances ≥ 0.1 %	
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	

CE - 18 -

Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 2001010
EN 14041:2004 / AC2006
1658

www.wineo.de

EMISSIONS DANS L'AIR INTÉRIEUR



Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

DGNB NAVIGATOR

Registrierungs-Code
NAPCCU

www.dgnb-navigator.de

GREENGUARD

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS
UL GREENGUARD
GOLD

THIRD-PARTY VERIFIED
EPD

Institut Bauen und Umwelt e.V.

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.