

TECHNICAL CHARACTERISTICS

PURLINE | wineo 1200 Multi-Layer

Long-lasting multi-layer flooring according to ISO 20326 for glueless installation

wineo

	wineo 1200 wood XXL Multi-Layer	wineo 1200 stone XL Multi-Layer		
Format	1845 x 237 mm	913 x 488 mm		
Product thickness	9 mm	9 mm		
Weight	~ 9.1 kg/m²	~ 8.9 kg/m²		
Profile connection	Fold-Down 	LocTec 		
Planks / m² per box	5 / 2.19 m²	5 / 2.23 m²		
Boxes / m² per pallet	48 / 105.12 m²	34 / 75.82 m²		
Guarantee	You can find our guarantee conditions at – www.wineo.de			
Classification			Product composition	
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1	Top element • PU-top layer with surface-structure • decor paper • stabilisation
	Utilization class 33 EN ISO 10874	Commercial sector with heavy usage		
	Anti slip category DIN 51130	R 9		
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	2	Profile connection wood XXL – Fold-Down stone XL – LocTec
	Light fastness EN ISO 105-B02	~ 7		
	Residual indentation EN ISO 24343-1	≤ 0.10 mm	3	Core board Swell-protected Aqua-Protect® HDF core board 
	Castor chair test EN 425	25000 revolutions no damage with rolls type W	4	Underlay material Integrated underlay soundPROTECT
	Thermal resistance EN 12667	0.06 (m²K)/W	  www.blauer-engel.de/uz176 	
	Impact sound reduction EN ISO 10140	~ 15 dB		
	Reflected walking sound reduction	~ 29 %		
REACH	free from SVHC substances ≥ 0.1 %			
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203			
 Windmüller GmbH Charles-Lindbergh-Ring 13 D-32756 Detmold DOP: 2001011 EN 14041:2004 / AC2006 1658  www.wineo.de ÉMISSIONS DANS L'AIR INTÉRIEUR*  Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)				

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.