

TECHNICAL CHARACTERISTICS

PURLINE wineo 1000 to click				wineo		
Permanently elastic polyurethane flooring according to EN 16776 free of chlorine, solvents and plasticizers						
	to click	wood L	wood XL	stone L		
Format		1295 x 195 mm	1507 x 246 mm	642 x 330.5 mm		
Product thickness		5 mm	5 mm	5 mm		
Profile connection	Fold-Down 	Fold-Down 	LocTec 			
Weight		9 kg/m²	9 kg/m²	9 kg/m²		
Planks / m² per box		8 / 2.02 m²	6 / 2.22 m²	10 / 2.12 m²		
Boxes / m² per pallet		56 / 113.12 m²	48 / 106.56 m²	52 / 110.24 m²		
Guarantee	You can find our guarantee conditions at – www.wineo.de					
Classification					Product composition	
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage			1	Top element • PU-top layer with surface structure • decor paper • stabilisation
	Utilization class 32 EN ISO 10874	Commercial sector with average usage				
	Anti slip category DIN 51130	R 9			2	Profile connection Fold-Down locking (wood) LocTec locking (stone)
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time				
	Light fastness EN ISO 105-B02	~ 7			3	Base layer ecuran high performance composite material
	Residual indentation EN ISO 24343-1	~ 0.05 mm				
	Effect of a furniture leg EN 424	Foot type 0 – no visible change			4	Backing Integrated Fleece TEC-System
	Castor chair test EN 425	25000 revolutions no damage with rolls type W			  www.blauer-engel.de/uz120	
	Thermal resistance ISO 8302	0.01 (m²K)/W				
	Impact sound reduction EN ISO 10140	~ 6 dB ~ 16 dB in the system with silentCOMFORT				
	Dimension stability EN ISO 23999	~ 0.10 %				
REACH		free from SVHC substances ≥ 0.1 %				
Disposal		Private: possible with normal domestic refuse Commercial: Refuse-key-no. AVV 170203				
 Windmüller GmbH Nord-West-Ring 21 D-32832 Augustdorf DOP: 2001010 EN 14041:2004 / AC2006 1658  www.wineo.de  Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)  Registrierungs-Code NAPCCU www.dgnb-evalgate.de     Institut Bauen und Umwelt e.V.  						
Relevant Information: • Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C. • Cleaning and care: See separate cleaning & care instruction. • Technical subjects can be changed by Windmüller GmbH.						