

# TECHNICAL CHARACTERISTICS

## PURLINE organic flooring | wineo 1200 to click (Semi-Rigid)

Permanently elastic polyurethane flooring according to EN 16776  
Without the addition of chlorin, without plasticisers or solvents.

# wineo

	<b>wineo 1200</b> wood XL V4	<b>wineo 1200</b> stone XL	
<b>Format</b>	1507 x 246 mm	1000 x 500 mm	
<b>Product thickness</b>	5 mm	5 mm	
<b>Weight</b>	9 kg/m <sup>2</sup>	9 kg/m <sup>2</sup>	
<b>Profile connection</b>	Fold-Down	LocTec	
<b>Planks / m<sup>2</sup> per box</b>	6 / 2.22 m <sup>2</sup>	6 / 3.00 m <sup>2</sup>	
<b>Boxes / m<sup>2</sup> per pallet</b>	48 / 106.56 m <sup>2</sup>	36 / 108.00 m <sup>2</sup>	
<b>Guarantee</b>	30 years – Guarantee for private use according to Windmüller warranty conditions – <a href="http://www.wineo.de">www.wineo.de</a>		

Classification		Product composition
<b>Utilization class 23</b> EN ISO 10874	Domestic area with intensive usage	<b>1 Top element</b> <ul style="list-style-type: none"> <li>• PU-top layer with surface structure</li> <li>• decor paper</li> <li>• stabilisation</li> </ul>
<b>Utilization class 33</b> EN ISO 10874	Commercial sector with heavy usage	
Scratch resistance EN 16776, annex A	Utilization class 33: ≥ 6 N	
<b>R9</b> Anti slip category DIN 51130	R 9	<b>2 Profile connection</b> wood XL – Fold-Down stone XL – LocTec
<b>Staining and chemical resistance</b> EN ISO 26987	Very good resistance according to the concentration and residence time	
<b>Light fastness</b> EN ISO 105-B02	~ 7	<b>3 Base layer</b> ecuran high performance composite material Tele-Stop feature
<b>Residual indentation</b> EN ISO 24343-1	≤ 0.10 mm	
<b>Effect of a furniture leg</b> EN 424	in test: Foot type 2 – no visible change	<b>4 Backing</b> Integrated Fleece TEC-System
<b>Castor chair test</b> EN ISO 4918	25000 revolutions no damage with rolls type W	
<b>Thermal resistance</b> ISO 8302	0.01 (m <sup>2</sup> K)/W	
<b>Impact sound reduction</b> EN ISO 10140	in test	
<b>Dimension stability</b> EN ISO 23999	≤ 0.15 %	
<b>REACH</b>	free from SVHC substances ≥ 0.1 %	
<b>Disposal</b>	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	

**CE** - 18 -

Windmüller GmbH  
Nord-West-Ring 21  
D-32832 Augustdorf

DOP: 2001010  
EN 14041:2004 / AC2006  
1658

**HCHO**

±2kV

±0,25 W/mk

[www.wineo.de](http://www.wineo.de)

**EMISSIONS DANS L'AIR INTÉRIEUR**

**A+**

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

**DGNB**  
NAVIGATOR

Registrierungs-Code  
NAPCCU  
[www.dgnb-navigator.de](http://www.dgnb-navigator.de)

**GREENGUARD**

GREENGUARD GOLD

**THE INDOOR CLIMATE LABEL**

**emissionsgeprüft**  
**schadstoffgeprüft**

**PREMIUM**

**Bewertung**  
**basis**  
eco-bau

**THIRD-PARTY VERIFIED**  
**EPD**

Institut Bauren und Umwelt e.V.

**floor score**

CERTIFIED BY  
SCS Global Services

**EMISSION CLASS FOR BUILDING MATERIAL**  
**M1**

### Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.