


# TECHNICAL CHARACTERISTICS

## PURLINE | wineo 1000 to glue
























Permanently elastic polyurethane flooring according to EN 16776  
Without the addition of chlorin, without plasticisers or solvents.

# wineo

	wood L	wood XL	stone L
<b>Format</b>	1298 x 199 mm	1500 x 250 mm	645 x 335 mm
<b>Product thickness</b>	2.2 mm	2.2 mm	2.2 mm
<b>Weight</b>	3.0 kg/m <sup>2</sup>	3.0 kg/m <sup>2</sup>	3.0 kg/m <sup>2</sup>
<b>Planks / m<sup>2</sup> per box</b>	20 / 5.17 m <sup>2</sup>	14 / 5.25 m <sup>2</sup>	22 / 4.75 m <sup>2</sup>
<b>Boxes / m<sup>2</sup> per pallet</b>	60 / 310.20 m <sup>2</sup>	56 / 294 m <sup>2</sup>	66 / 313.50 m <sup>2</sup>



**Guarantee** You can find our guarantee conditions at – [www.wineo.de](http://www.wineo.de)

Classification		Product composition
	<b>Utilization class 23</b> EN ISO 10874	<b>1</b>  <b>Top element</b> <ul style="list-style-type: none"> <li>• PU-top layer with surface structure</li> <li>• decor paper</li> <li>• stabilisation</li> </ul>
	<b>Utilization class 32</b> EN ISO 10874	
	Scratch resistance EN 16776, annex A	
	<b>R9</b> Anti slip category DIN 51130	<b>2</b>  <b>Base layer</b> ecuran high performance composite material
	Staining and chemical resistance EN ISO 26987	
	Light fastness EN ISO 105-B02	<b>3</b>  <b>Backing</b> Integrated Fleece TEC System
	Residual indentation EN ISO 24343-1	
	Effect of a furniture leg EN 424	          
	Castor chair test EN 425	
	Thermal resistance ISO 8302	
	Impact sound reduction EN ISO 10140	
	Dimension stability EN ISO 23999	
	Flexural behaviour EN ISO 24344	
	REACH	
	Disposal	

**CE** - 18 -

Windmüller GmbH  
Nord-West-Ring 21  
D-32832 Augustdorf

DOP: 2001010  
EN 14041:2004 / AC2006  
1658



[www.wineo.de](http://www.wineo.de)

**ÉMISSIONS DANS L'AIR INTÉRIEUR**

**A+**

A+ A B C

Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

**DGNB NAVIGATOR**

Registrierungs-Code  
**NAPCCU**

[www.dgnb-navigator.de](http://www.dgnb-navigator.de)

**GREENGUARD**

GREENGUARD

**THIRD-PARTY VERIFIED EPD**

Institut Bauen und Umwelt e.V.

**Relevant Information:**

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 29 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.