



# TECHNICAL CHARACTERISTICS











## PURLINE organic flooring | wineo 1200 Multi-Layer


Long-lasting multi-layer flooring according to ISO 20326 for glueless installation

# wineo

	wineo 1200 wood XXL Multi-Layer	wineo 1200 stone XL Multi-Layer
<b>Format</b>	1845 x 237 mm	913 x 488 mm
<b>Product thickness</b>	9 mm	9 mm
<b>Weight</b>	~ 9.1 kg/m <sup>2</sup>	~ 8.9 kg/m <sup>2</sup>
<b>Profile connection</b>	Fold-Down 	LocTec 
<b>Planks / m<sup>2</sup> per box</b>	5 / 2.19 m <sup>2</sup>	5 / 2.23 m <sup>2</sup>
<b>Boxes / m<sup>2</sup> per pallet</b>	48 / 105.12 m <sup>2</sup>	34 / 75.82 m <sup>2</sup>
<b>Guarantee</b>	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de	



Classification		Product composition
	<b>Utilization class 23</b> EN ISO 10874	Domestic area with intensive usage
	<b>Utilization class 33</b> EN ISO 10874	Commercial sector with heavy usage
	Anti slip category DIN 51130	R 9
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time
	Light fastness EN ISO 105-B02	~ 7
	Residual indentation EN ISO 24343-1	≤ 0.10 mm
	Castor chair test EN 425	25000 revolutions no damage with rolls type W
	Thermal resistance EN 12667	0.06 (m <sup>2</sup> K)W
	Impact sound reduction EN ISO 10140	~ 15 dB
	Reflected walking sound reduction	~ 29 %
REACH	free from SVHC substances ≥ 0.1 %	
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	

- 1 Top element**
  - PU-top layer with surface-structure
  - decor paper
  - stabilisation
- 2 Profile connection**  
wood XXL – Fold-Down  
stone XL – LocTec
- 3 Core board**  
Swell-protected Aqua-Protect®  
HDF core board 
- 4 Underlay material**  
Integrated underlay soundPROTECT








[www.blauer-engel.de/uz176](http://www.blauer-engel.de/uz176)

**CE** - 21 -

Windmüller GmbH  
Nord-West-Ring 21  
D-32832 Augustdorf

DOP: 2001011  
EN 14041:2004 / AC2006  
1658

**C<sub>s1</sub>** **DS** **HCHO** **≤ 2 kV** **≥ 0.07 W/(mK)**

[www.wineo.de](http://www.wineo.de)

**ÉMISSIONS DANS L'AIR INTÉRIEUR\***

 **A+**

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

**TÜV PROFI CERT**

70 710 4061-5  
[www.proficert.com](http://www.proficert.com)

**TFI** emissionsgeprüft  
schadstoffgeprüft

**PREMIUM**

### Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.