

TECNICAL CHARACTERISTICS

wineo 600 Rigid				wineo	
Heterogeneous resilient-flooring for glueless installation - Covering type according to DIN EN 16511					
	wood	wood XL	stone XL		
Format	1212 x 186 mm	1507 x 234 mm	746 x 477 mm		
Product thickness	5 mm	5 mm	5 mm		
Planks, tiles / m ² per box	8 / 1.80 m ²	6 / 2.12 m ²	6 / 2.14 m ²		
Boxes / m ² per pallet	56 / 100.80 m ²	48 / 101.76 m ²	44 / 94.16 m ²		
Guarantee	You can find our guarantee conditions at - www.wineo.de				
Classification				Product composition	
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1	Surface seal	
	Utilization class 32 EN ISO 10874	Commercial sector with average usage	2	Surface texture Various embossings	
	Wear layer binder content EN ISO 10582	Typ I	3	Wear layer Thickness 0.4 mm	
	Anti slip category DIN 51130	R 9	4	Design Decor film	
	Resistance to staining EN 438-2	Group 1 + 2: grade 5 Group 3: grade 4	5	Elastic top layer	
	Light fastness EN ISO 105-B02	Light fastness (procedure 2) ≥ 6	6	Core board	
	Residual indentation EN ISO 24343-1	≤ 0.1 mm	7	Profile connection Connect technology 	
	Thermal resistance EN 12667	~ 0.05 (m²K)/W without underlay mat ~ 0.06 (m²K)/W with silentRIGID	8	Elastic bottom layer	
	Castor chair test ISO 4918	25000 revolutions no damage with rolls type W	9	Underlay material silentRIGID (available separately)	
	Anti-static properties EN 1815	≤ 2 kV	   		
	Impact sound reduction EN ISO 16251-1	~ 6 dB without underlay mat up to 13 dB with silentRIGID			
	Dimensional stability EN ISO 23999	≤ 0,1%			
	REACH	free from SVHC substances ≥ 0.1 %			
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203			
 - 25 -  www.wineo.de ÉMISSIONS DANS L'AIR INTÉRIEUR*  Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)					

Relevant information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.