TECHNICAL CHARACTERISTICS

PURLINE | wineo 1200 Multi-Layer

Long-lasting multi-layer flooring according to EN 16511 for glueless installation

wineo

	wineo 1200 wood XXL Multi-Layer	wineo 1200 stone XL Multi-Layer
Format	1845 x 237 mm	913 x 488 mm
Product thickness	9 mm	9 mm
Weight	~ 9.1 kg/m²	~ 8.9 kg/m²
Profile connection	Fold-Down	LocTec
Planks / m² per box	5 / 2.19 m²	5 / 2.23 m²
Boxes / m² per pallet	48 / 105.12 m²	34 / 75.82 m²
Guarantee	You can find our guarantee conditions at – www.wineo.de	



Classification

Utilization class 23 EN ISO 10874	Domestic area with intensive usage
Utilization class 33 EN ISO 10874	Commercial sector with heavy usage
Anti slip category DIN 51130	R 9
Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time
Light fastness EN ISO 105-B02	≤ 6
Residual indentation EN ISO 24343-1	≤ 0.10 mm
Castor chair test EN 425	25000 revolutions no damage with rolls type W
Thermal resistance EN 12667	0.06 (m²K)W
Impact sound reduction EN ISO 10140	~ 15 dB
Reflected walking sound reduction	~ 29 %
REACH	free from SVHC substances ≥ 0.1 %
Disposal	Private: possible with normal domestic refuse Commercial: Refuse-key-no. AVV 170203

Product composition

1	**Top element** • PU-top layer with surface-structure • decor paper • stabilisation
2	**Profile connection** wood XXL – Fold-Down stone XL – LocTec
3	**Core board** Swell-protected Aqua-Protect® HDF core board
4	**Unterlay material** Integrated underlay soundPROTECT

CE
Windmöller GmbH
Charles-Lindbergh-Ring 13
D-32756 Detmold
- 25 -
DOP: 2001011
EN 14041:2004 / AC2006
1658
Cfl-s1 | DS | E1 HCHO | ≤ 2 kV | ≥ 0,07 W/(mK)
www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR
A+
A+ A B C
Information representative des emissions dans l'air interieur des substances volatiles presentant un risque de toxicite par inhalation, sur une echelle de classe allant de C (fortes emissions) a A+ (tres faibles emissions)

full scope CERTIFIED cradle to cradle bronze version 4.1 C2CCERTIFIED.ORG

BLAUER ENGEL DAS UMWELTZEICHEN
www.blauer-engel.de/uz176

TÜV PROFI CERT 70 710 4061-5
emissionsgeprüft schadstoffgeprüft PREMIUM

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmöller GmbH.